

Product Name: ISOLATEK® Type DC/F

ISOLATEK® Type DC/F, ISOLATEK® Type II, ISOLATEK®Type HP

Product Use/Class: Spray-Applied Fire Resistive Materials (SFRM)

Manufacturer: United States Mineral Products Company

dba Isolatek International 41 Furnace Street Stanhope, NJ 07874 USA

(973)-347-1200

In Case of Emergency Call: CHEMTREC

800.424.9300 (USA) +1 703.527.3887 (Int'I)

Effective Date:

October 6, 2015

Preparer:

R&D Department

Supersedes:

January 30, 2015

Section 2 - Hazards Identification

GHS Classification:

Hazard ClassHazard CategoryRoute of ExposureSkin Irritation2SkinSkin Sensitizer1SkinEye Irritation2BEyeInhalation Toxicity4Nose/Mouth

Global Harmonization Labeling and Classification:

Signal word: Warning

Hazard Symbol(s): GHS07



Overview: This product is not expected to produce any unusual hazards during normal use. Exposure to high dust levels may irritate the skin, eyes, nose, throat, or upper respiratory tract. As product may contain trace amount of crystalline silica, prolonged exposure to respirable crystalline silica may cause cancer.

Primary Route(s) of Entry: Skin Contact, Skin Absorption, Inhalation, Ingestion, Eye Contact

Medical Conditions Prone to Aggravation by Exposure: Sensitive skin; respiratory conditions

Hazard Statements:				
H303	May be harmful if swallowed.			
H313	May be harmful in contact with skin.			
H320	Causes eye irritation.			
H335	May cause respiratory irritation.			
H373	May cause damage to organs through prolonged or repeated exposure.			

IS STATEK Brand

Precautionary Statements:						
P202	o not handle until safety precautions have been read and understood.					
P261	Avoid breathing dust/ fumes/ gas/ mist/ vapours/ spray.					
P271	Use only outdoors or in a well ventilated area.					
P280	/ear protective gloves/ protective clothing/ eye protection/ face protection.					
P284	/ear respiratory protection.					
P402+P403	re in a dry place. Store in a well ventilated place.					
EUH401	To avoid risks to human health and the environment, comply with the instructions for use.					

Response:	
P301+P330 P331+P312	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/ physician if you feel unwell.
P302+P352+ P332+P313+ P363	IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/ attention. Wash contaminated clothing before reuse.
P304+P340+ P342+P313	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Get medical advice/ attention.
P305+P351+ P338+P337+ P313	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Storage:	
P402+P403+ P232	Store in a dry place. Store in a well ventilated place. Protect from moisture.

Disposal:	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations (see section 13).

Section 3 – Composition / Information On Ingredients

Chemical Name	CAS Number	Wt. % (Max.)
Slag Wool	65997-17-3	50 - 90
Portland Cement	65997-15-1	10 – 50
Calcium Sulfate Hemihydrate	26499-65-0	1 - 10
Crystalline Silica	14808-60-7	<1

Section 4 - First Aid Measures

General – If irritation or other symptoms occur or persist from any route of exposure, remove the affected individual from the area, see a physician/get medical attention.

First Aid - Skin Contact: Wash with soap and water. Remove contaminated clothing. If persistent irritation occurs, seek medical attention.

First Aid - Eye Contact: Flush eyes thoroughly with copious amounts of water. Seek medical attention if irritation persists.

First Aid – Inhalation: Remove to fresh air. Seek medical attention if irritation persists.

First Aid - Ingestion: Do not induce vomiting. Rinse mouth out with water. Seek medical attention if irritation persists.

Protection of first aid responders: Wear proper personal protective clothing and equipment.



Section 5 - Fire Fighting Measures

Extinguishing Media: Not Applicable. Product will not burn.

Unusual Fire & Explosion Hazards: None.

Special Firefighting Procedures: None.

Section 6 – Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Sweep up material and place in disposal containers. Avoid inhalation of dust. Dispose of material in accordance with all federal, state, and local regulations. Use personal protective equipment as necessary.

Section 7 - Handling And Storage

Precautions for safe handling: Avoid inhalation of dust. Avoid skin & eye contact. Wear skin and eye protection during use. Use normal personal hygiene to remove materials, contaminants; wash clothing separately before re-use.

Conditions for safe storage: Keep dry. Keep containers closed when not in use. Store in a cool, dry place with adequate ventilation.

Section 8 – Exposure Controls / Personal Protection

Permissible Exposure Limits

Chemical Name CAS Number		OSHA PEL	ACGIH TLV	NIOSH	Mexico
Slag Wool 65997-17-3		15 mg/m³ TWA (Total Dust) 5 mg/m³ (Respirable Fraction)	1 f/cc TWA	5 mg/m³ TWA (Total Dust)	N/E
Portland Cement	15 mg/m³ TW/A		10 mg/m3 TWA (Chemical is a particulate matter containing no asbestos and <1% crystalline silica.	10 mg/m³ TWA (Total Dust)	N/E
Calcium Sulfate 26499-65-0 Hemihydrate		15 mg/m³ TWA (Total Dust) 5 mg/m³ (Respirable Fraction)	15 mg/m3 TWA (Chemical is a particulate matter containing no asbestos and <1% crystalline silica.	10 mg/m³ TWA (Total Dust) 5 mg/m³ (Respirable Fraction)	10 (Respirable Fraction)
Crystalline Silica	14808-60-7	30 mg/m ³ %SiO2 +2 (Total Dust) 250 mppcf %SiO2 +5 (Respirable) 10 mg/m ³ %SiO2 +2 (Respirable Fraction)	0.025 mg/m ³ TWA (Respirable Fraction)	0.05 mg/m³ TWA (Total Dust) 0.05 mg/m³ TWA Respirable Fraction)	0.010mg/m ³ TWA (Total Dust)

Engineering Controls: Exhaust fans may be necessary when mixing in enclosed areas.

Respiratory Protection: Wear a proper disposable dust mask to prevent exposure above the limits specified.

Skin Protection: Wear gloves and use hand creams to prevent dry skin.

Eye Protection: Wear proper eye protection; at minimum, safety glasses with side shields.

Work / Hygienic Practices: Use bag opening procedures which minimize dust release. Use anti-slip surfaces on working platforms – material is slippery when wet.



Section 9 - Physical And Chemical Properties

Appearance: White to charcoal

Odor: Low odor pH: 10-13 Melting Point (°F): >1800°F (981°C) Not Applicable Boiling Point (°F): Flash Point: Not Applicable **Evaporation Rate:** Not Applicable Not Applicable Flammability: Not Applicable **Lower Explosive Limit:** Not Applicable **Upper Explosive Limit:** Vapor Pressure (mm Hg): Not Applicable Bulk Density (kg/mm3) Not Applicable

Solubility in Water: Low

Specific Gravity (H₂O=1): Not Applicable

Physical State: Solid

Hazardous Polymerization:

% Volatiles: Not Applicable Viscosity Not Applicable Auto ignition temperature Not Applicable

Section 10 - Stability And Reactivity

Chemical Stability (under normal conditions): Stable Possibility of Hazardous Reactions: No

Conditions to Avoid: Contact with strong acids

Incompatibility: Strong Acids

Hazardous Decomposition Products: Stable under normal conditions. Trace amounts of carbon and nitrogen oxide

compounds may release under fire.

No polymerization will occur.

Section 11 - Toxicological Information

Carcinogenicity	Carcinogenicity IARC		NTP		OSHA	LD50/LC50	
Chemical Name	Group 1	Group 2	Group 3	Known	Suspect		
Slag Wool	No	No	Yes (not classifiable as to human carcinogenicity)	No	No	No	No Data Available
Portland Cement	No	No	No	No	No	No	No Data Available
Calcium Sulfate Hemihydrate	No	No	No	No	No	No	No Data Available
Crystalline Silica	Yes	No	No	Yes	No	Yes	No Data Available

Section 12 - Ecological Information

Ecological Information: No data available.

Section 13 - Disposal Considerations

Disposal Information: For waste disposal purposes, this product is not known to be designated as hazardous by current provisions under RCRA. Dispose of in accordance with federal, state and local regulations.



Section 14 - Transportation Information

Proper Shipping Name: Not Applicable Technical Name: Not Applicable **Hazard Class**: Non-Hazardous UN/NA Number: Not Applicable **Additional Notes:** None

Section 15 - Regulatory Information

U.S. Federal Regulations	Immediate Health (Acute)	Delayed Health (Chronic)	FIRE	PRESSURE	REACTIVE
SARA 311/312	No	Yes	No	No	No

	State Hazardous Substance List							
	CAS Number	CA	MA	MN	NJ	PA	RI	
U.S. State Regulations	65997-17-3	No	No	No	No	No	No	
	65997-15-1	No	No	No	No	No	No	
	26499-65-0	No	No	No	No	No	No	
	14808-60-7	Yes	Yes	Yes	Yes	No	Yes	

International Regulations as Follows:

Chemical Inventory Status

All chemicals in this product are listed or exempt from listing in the following countries:

U.S	Canada		Europe	Australia	Korea
TSCA	DSL	NDSL	EINECS ELINCS	AICS	ECL
Yes	Yes	No	Yes	Yes	Yes

CANADIAN WHIMIS

This SDS has been prepared in compliance with Controlled Product Regulations and contains all information required.

CANADIAN WHMIS CLASS: D2A

HMIS Rating






Section 16 – Other Information

N/E - Non Established N/A - Not Applicable

NFPA:



Prepared By: Research Department, U.S.A.

Telephone: (973) 347-1200

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. VENDOR SPECIFICALLY DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event shall the vendor be liable for special, indirect or consequential damages.

Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in this data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes all risks in his use of the material.

